

P3 Deflect™ 120



INFINAM® 

An Evonik product.

High-temperature photopolymer with good strength for functional parts, from Evonik INFINAM®.

Our first photopolymer from Evonik is a strong, heat-resistant material that addresses applications where a combination of high-temperature resistance and good elongation at break are crucial. P3 Deflect 120 has low viscosity and high green strength, which make it suitable for parts with challenging geometries such as wiring housings, connectors, or mold tooling.

Key Benefits

- High HDT, 121°C (250°F) with good elongation at break
- Very stiff and high green strength
- Easy to print + single component material
- Color: Black



	Unit	Value	Method
MECHANICAL PROPERTIES			
Ultimate Tensile Strength	MPa	100	ASTM D638
Young Modulus	MPa	3000	ASTM D638
Elongation at Break	%	4	ASTM D638
Flexural Modulus	MPa	3715	ASTM D790
Flexural Stress at 5% Strain	MPa	132	ASTM D790
Izod Notched Impact Strength	J/m	15	ASTM D256
THERMAL PROPERTIES			
Heat Deflection Temperature (0.455 MPa)	°C	121	ASTM D648
PHYSICAL PROPERTIES			
Ec / Dp	mJ/cm ² / mm	3.48 / 0.12	Internal
Shore Hardness (3s)	-	88	ASTM D2240
Liquid Viscosity at 25°C	mPa · s	450	ASTM D7867

USA - Headquarters

7665 Commerce Way
Eden Prairie, MN 55344, USA
+1 952 937 3000

ISRAEL - Headquarters

1 Holtzman St., Science Park
PO Box 2496
Rehovot 76124, Israel
+972 74 745 4000

stratasys.com

ISO 9001:2015 Certified

EMEA

Airport Boulevard B 120
77836 Rheinmünster, Germany
+49 7229 7772 0

ASIA PACIFIC

7th Floor, C-BONS International Center
108 Wai Yip Street Kwun Tong Kowloon
Hong Kong, China
+ 852 3944 8888



GET IN TOUCH.

www.stratasys.com/contact-us/locations

